



Bourdon tube pressure gauges for chemical applications RF63ChGly

Part no. 85107702

Bourdon tube pressure gauge for chemical applications type D7 with glycerine filling

benefits

- for chemical and process engineering applications
- measuring system fully welded to housing
- extremely robust design
- can be used in case of heavy vibrations and high, dynamic pressure loads
- tightness-tested with helium
- DNV- and GOSSTANDART-certified
- Ex version (optional)

Application

For corrosive gaseous and liquid media which are not highly viscous and do not crystallise; suitable for corrosive environments. For measurements in areas with high vibration levels and high, dynamic pressure loads.

! For measuring gas or vapour, observe the table "Selection Criteria as per EN 837-2" (see appendix)!

Technical Specifications

Type

D7

Nominal size

63

accuracy class (EN 837-1/6)

1.6

ranges (EN 837-1/5)

see ordering table

application area

static load: $\frac{3}{4}$ x full scale value

dynamic load: $\frac{2}{3}$ x full scale value

short-term: Full scale value

Operating temperature range

Medium: max. 100 °C

Ambient: -20/+60 °C

Temperature performance

Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:

at rising temperature approx. ± 0.4 %/10 K

falling temperature approx. ± 0.4 %/10 K
of full scale value

Degree of protection

IP 54 (EN 60529) with housing vent (< 25 bar)

standard version

Connection

Stainless steel 316 L, bottom

Measuring element

Bourdon tube, stainless steel 316 Ti/316 L

≤ 60 bar: "C" type tube

> 60 bar: helical tube

tightness-tested with helium

movement

Stainless steel

Dial

Aluminium, white

Scaling: black

Pointer

Aluminium, black

Options

- Filling liquid silicone oil
- plastic window (NG 63)
- Back flange (NG 63)
- clamp fixing
- Ex version
- Crimped bezel, polished
- special scales
- other process connections

Housing

Stainless steel 304, with blow-out

bayonet bezel

NG 63

crimped bezel

Stainless steel 304

window

NG 63


Laminated safety glass

filling liquid

glycerine (99.5 %)

Technical Drawings

NG 50/63 – bottom connection



Dimensions (mm)

NG	a	b	ϕc	c1	c2	D	G	h	s	SW
50	10,5	28	5	2	13	53	G1/4B	46	4,5	14
63	11,5	32	5	2	13	68	G1/4B	53	7	14

Versions

Range	Mounting type	Type	Part number
-1/+15 bar	direct	RF63ChGly D702	85107702

- in-stock items
- Non-stock items