




## Standard capsule pressure gauges KP160

Part no. 35161401

Standard capsule pressure gauges Type D4

### benefits

- with zero correction
- optional overpressure and/or underpressure safety 10 x FSD
- extremely low measuring ranges from 0/6 mbar
- GOSSTANDART-certified

### Application

For gaseous, dry media which do not attack copper alloys.

! For measuring gas or vapour, observe the table "Selection Criteria as per EN 837-2" (see appendix)!

### Technical Specifications

#### Type

D4

#### Nominal size

160

#### accuracy class (EN 837-3/6)

1.6

#### ranges (EN 837-3/5)

see ordering table

#### application area

static load: Full scale value

dynamic load: 0.9 x full scale value

overload safety: 1.3 x full scale value

#### Operating temperature range

Medium: max. 60 °C

Ambient: -20/+60 °C

#### Temperature performance

Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:

at rising temperature approx.  $\pm 0.6 \text{ } \%/10 \text{ K}$

falling temperature approx.  $\pm 0.6 \text{ } \%/10 \text{ K}$

of full scale value

#### Degree of protection

NG 160

IP 33 (EN 60529)

#### Connection

Brass, bottom

#### Measuring element

Capsule element, CuBe alloy

#### movement

Brass

#### Zero correction

from the front

**Seal**  
NBR (Perbunan)

**Dial**  
Aluminium, white  
Scaling: black

**Pointer**  
Aluminium, black

**Housing**  
Stainless steel 304

**bayonet bezel**  
Stainless steel 304


**window**  
D401  
Instrument glass

## Options

- overpressure and underpressure safety 10 x FSD
- back flange
- Panel mounting bezel, with window, plastic
- 3-hole fixing, panel mounting bezel with window, plastic
- throttle screw
- Reference pointer
- special scales
- other process connections

## Technical Drawings

### Bottom connection



### Dimensions (mm)

| NG  | a    | b  | φc | c1 | c2 | G                 | h   | SW |
|-----|------|----|----|----|----|-------------------|-----|----|
| 63  | 10,8 | 40 | 5  | 2  | 13 | G $\frac{1}{4}$ B | 53  | 14 |
| 100 | 15,6 | 49 | 6  | 3  | 20 | G $\frac{1}{2}$ B | 86  | 22 |
| 160 | 17,5 | 50 | 6  | 3  | 20 | G $\frac{1}{2}$ B | 116 | 22 |

Versions

| Range        | Mounting type | Type          |   | Part number |
|--------------|---------------|---------------|---|-------------|
| -600/+0 mbar | direct        | KP160<br>D401 | ● | 35161401    |

- in-stock items
- Non-stock items