



Digital pressure gauges DIM 20

Part no. 32513

universal digital pressure gauge

benefits

- universal test pressure gauge with high measuring accuracy
- high flexibility due to selectable units: bar/mbar/psi/inHg/mmHg/cmHg/kPa/MPa/mWC
- Min./max. memory
- intuitive operation via menus
- Display can be rotated by 330°
- Zero and full scale can be calibrated
- adjustable auto-off function



Application

For high-precision electronic pressure measurement with local digital display, for applications such as hydraulics, pneumatics, mechanical and plant engineering. Compact microprocessor-controlled pressure gauge with thick film ceramic measuring cell. The signal received from the pressure sensor is processed by the microprocessor, converted into the desired unit and displayed. Each device is shipped with its own measurement log.

Description

Compact microprocessor-controlled pressure gauge with thick-film ceramic measuring cell. The signal received from the pressure sensor is processed by the microprocessor, converted into the desired unit and displayed. Each device is shipped with its own measurement log.

Technical Specifications

functions

units switching,
Min./max. value memory,
zero and full scale calibration,
adjustable auto-off function,
adjustable decimal point,
battery status indication

Indication of measured values

bar, mbar, psi, inHg, mmHg, cmHg, kPa, MPa oder mWS
selectable pressure unit

Display

multi-line LCD,
4.5 digit, numeric, for displaying the measured value (character height 9.5 mm) – line 1,
6-digit, alphanumeric, for displaying additional information (character height 6.8 mm) and additional symbols – line 2,
Display can be rotated by 330°

Measuring accuracy

Deviation from the characteristic curve according to IEC 60770 – limit point calibration (non-linearity, hysteresis, repeatability)
± 0.5 % FSO (BFSL)

Measuring range

0/250 bar

at least 1.5 x FS

≤ 160 bar at least 2.5 x FS
 > 160 bar at least 1.5 x FS

Medium: -20/+125 °C
Ambient: -20/+45 °C
Storage: -30/+80 °C

 $\leq \pm 0.5 \% \text{ FSO}/10 \text{ K}$ In compensated range 0/70 °C

Measuring rate: 5 Hz

G¹/₄B (EN 837-1/7.3, bottom)

Housing: PA6, glass-loaded
Process connection: Stainless steel 304
diaphragm: ceramic (Al₂O₃ 96 %)
Seal: FKM

IP 51 (EN 60529)

1 x 3.6 V lithium battery
service life up to 5 years, depending on use

EMC Directive 2014/30/EU
RoHS Directive 2011/65/EU
Pressure Equipment Directive 2014/68/EU module A

Dimensions (in mm)

32513