

PRODUCT DATA SHEET

EVERBUILD® Decorators Flexible Filler

FAST DRYING, ACRYLIC BASED FILLER THAT REMAINS PERMANENTLY FLEXIBLE

PRODUCT DESCRIPTION

EVERBUILD® Decorators Flexible Filler is a filler that can be overpainted with all paint types, or covered over with wallpaper. No sanding down is required.

USES

- For sealing and filling cracks and gaps prior to decorating.
- For use around skirting boards, ceiling cornices, window and door frames, stair treads and risings and fixtures adjoining walls.
- Can be used to fill damage plaster.

CHARACTERISTICS / ADVANTAGES

- Fast drying - can be overpainted in 1 hour.
- Permanently flexible.
- Easy water clean up.
- Excellent slump resistance.

Elongation at break	>100% ISO8339
Hardness (Shore A)	Approximately 50
Slump Resistance	No slump to ISO7390
Movement Accommodation	Low (+/- 5%)
Tack Free Time	15 to 60 mins, dependent on thickness, ambient temperature and humidity

Chemical Resistance

Dilute acids	Fair
Aliphatic Hydrocarbons	Fair
Dilute Alkaline	Fair
Aromatic Hydrocarbons	Poor

APPROVALS / STANDARDS

Certified under the harmonized European standard EN15651 for façade interior applications in compliance with the Construction Product Regulation.

PRODUCT INFORMATION

Chemical Base	Ready to use thixotropic paste
Packaging	290ml cartridge 200ml Easi Squeeze Tube
Shelf Life	Up to 36 months when stored in unopened cartridges under cool dry conditions. AVOID FROST
Storage Conditions	Store in cool dry conditions and protect from frost
Density	1.6 - 1.7 g/cm ³
Solid Content	~81%
Ambient Air Temperature	+4°C to +40°C
Substrate Temperature	-15°C to +75°C
Drying time	3 to 5 days, dependent on thickness, ambient temperature and humidity

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

All surfaces must be clean, dry and dust free. All loose or flaking surface coatings, and old sealant and mastic joints, should be removed before application. Highly porous substrates such as new plaster should first be primed with a dilution of filler with water at a ratio of 1:2. Can be applied to slightly damp surfaces.

APPLICATION

Cartridge: cut the tip of the cartridge taking care not to damage the thread. Apply nozzle and cut cleanly at an angle of 45° with an opening slightly larger than the gap to be sealed. Apply using a standard sealant gun. Best results will be obtained by keeping an even pressure on the gun trigger and keeping the gun at a constant angle to the surface being sealed.

Easi-squeeze tube: cut the tip of the tube with an opening slightly larger than the gap to be sealed. Squeeze the tube to apply, keeping the tip at a constant angle to the surface being sealed.

Smooth down within 15 minutes of application using a wetted spatula, piece of wood or wetted finger. Care should be taken at this point not to saturate the surface as this will delay drying. Any excess sealant etc. can be removed using a sponge and warm water. Can be overpainted after 1 hour.

LIMITATIONS

- Not for use in conjunction with bitumen or asphalt.
- Do not attempt to abrade when cured.
- Do not overpaint until a surface skin has formed.
- Note: this product is flexible. Certain poor quality paints (especially certain vinyl matts) have very little movement in the dry film. It is possible for the dry paint film to crack if movement is excessive.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

Product Data Sheet
EVERBUILD® Decorators Flexible Filler
June 2018, Version 02.01
020406010020000038



BUILDING TRUST



EVERBUILDDecoratorsFlexibleFiller-en-GBEVER-(06-2018)-2-1.pdf