

BUILDING TRUST

Everbuild Tecnic[®] Fire Sealant 300 DECLARATION OF PERFORMANCE No. 23513702

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	300
2	INTENDED USE/S	Sealants for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for interior applications only
3	MANUFACTURER:	Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Industrial Estate Leeds, LS9 0SW
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	4
6a	HARMONISED STANDARD:	BS EN 15651-1:2012
	Notified body/ies:	N/A

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	NPD	3	
Water tightness and air tightness			
Resistance to flow	≤ 5 mm	4	
Loss of volume	≤ 45 %	4	
Tensile properties (i.e. elongation): - at break at (23 °C)	≥ 25 %	4	EN15651-
Durability	Pass	4	1:2012
Release of dangerous chemicals	See sds		


8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas Function: Technical Product Coordinator At Leeds on 30 June 2021 Name : Emma Taylor Function: Product Manager At Leeds on 30 June 2021

End of information as required by Regulation (EU) No 305/2011



BUILDING TRUST

	(F	
	14 Everbuild Building Products	
	DoC No. 23513	
	BS EN15651-1:2	
	Notified Body I	
Sealant only	ts for non-structural use in joints in buildings and pedestri	an walkways Part 1: Sealants for interior application
	Reaction to fire	NPD
	Water tightness and air tightness	
	Water tightness and air tightness Resistance to flow	≤ 5 mm
		≤ 5 mm ≤ 45 %
	Resistance to flow	
	Resistance to flow Loss of volume Tensile properties (i.e. elongation): - at break at (23	<u>≤ 45 %</u>
	Resistance to flow Loss of volume Tensile properties (i.e. elongation): - at break at (23 °C)	≤ 45 %≥ 25 %
	Resistance to flow Loss of volume Tensile properties (i.e. elongation): - at break at (23 °C) Durability	 ≤ 45 % ≥ 25 % Pass
	Resistance to flow Loss of volume Tensile properties (i.e. elongation): - at break at (23 °C) Durability	 ≤ 45 % ≥ 25 % Pass
	Resistance to flow Loss of volume Tensile properties (i.e. elongation): - at break at (23 °C) Durability	 ≤ 45 % ≥ 25 % Pass

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance 300 23513702 2021/06 , ver. 02 1213

BUILDING TRUST

